

# High brightness halogen light source

	YP-150I	(YP-250I)
Irradiation area	30mm	60mm
Illuminance	More than 400,000 lx	
Irradiation distance	140mm	220mm
Light source	halogen lamp(Applying cold mirror)	
Lamp type	JCR15V150W	ELC24V250W
Average life	50hours	35 hours
color temperature	3,400K °	
Tone	White	
Environmental temperature	0 ~ 40	
Cooling method	Forced exhaust by propeller fan	
Connection pole size	12	20
Size	100(W) × 350 ± 10(H) × 116 (D) mm	120(W) × 390 ± 10(H) × 130(D)mm
Weight	1.85 kg	2.7 kg

Input voltage	AC100V 50/60Hz	AC100V 50/60Hz
Consumed power	200W	350W
Variable range	AC5 ~ 12V	AC10 ~ 22V
Environmental temperature	0 ~ 40	
Cooling method	Nature	Forced exhaust by propeller fan
Size	135(W) × 72(H) × 135(D)mm	135(W) × 72(H) × 260(D)mm
Weight	1.55 kg	2 kg
Others	Input cord :2m VCTF-cable 0.75sq (add a plug) Output cord :2m VCTF-cable 1.25sq (add metal connectors) Foot switch cord:3m (add metal connectors)	Input cord :2m VCTF-cable 0.75sq (add a plug) Output cord :2m VCTF-cable 1.25sq (add metal connectors)

**YAMADA KOGAKU KOGYO Co., LTD .**

1-28-1.NAKADAIMOTOMACHI.KAWAGOE.

SAITAMA.JAPAN E-mail:eigyo@yamada-opt.co.jp

TEL +81-49-243-4111 FAX +81-49-242-1526